



SPARTACOTE® Polyaspartic Pigments

DS-086.2-1015

A product brand of LATICRETE International, Inc.



1. PRODUCT NAME

SPARTACOTE® Polyaspartic Pigments

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: 1.866.966.1329

Toll Free Fax: 1.855.683.7257

Website: www.spartacote.com

3. PRODUCT DESCRIPTION

SPARTACOTE Polyaspartic Pigments are designed to be used exclusively with SPARTACOTE FLEX SB™, SPARTACOTE FLEX XT™ and SPARTACOTE FLEX PURE™ polyaspartic coatings. Available in 14 standard colors, these materials are manufactured through a proprietary process in which raw pigment elements are ground and subsequently combined with the highest quality polyaspartic resins available. Once ready for use, these concentrated pigments are dispersed directly into short-filled part A pigment base.

Uses

Suitable for interior or exterior applications

Advantages

- 14 standard colors, including safety colors
- UV stable, suitable for exterior applications
- Excellent color hide and retention
- Easy to use on-site color dispersion system

Suitable Substrates

As per SPARTACOTE Polyaspartic Coating

Packaging

- 1 qt (0.9 L) for .75 gal (2.8 L) part A base
- 1.25 gal (4.7 L) for 3.75 gal (14.2 L) pigment base

Available in 14 standard colors including safety colors pre-dispersed form upon request. SPARTACOTE FLEX SB polyaspartic coating is available in a White.

Approximate Coverage

See applicable SPARTACOTE Polyaspartic Coatings coverage chart

Shelf Life

12 months unopened. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun). Maintain a consistent storage temperature prior to application. Material should be kept in a cool dry place prior to application.

Limitations

Refer to data sheet for applicable SPARTACOTE Polyaspartic Coatings

Cautions

- Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

4. TECHNICAL DATA

Applicable Standards and Test Methods

Physical and Working Properties

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE International, Inc. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

5. INSTALLATION

Mixing

Note: Maintain a consistent storage temperature prior to application. Material should be kept in a cool dry place prior to application. Use only with SPARTACOTE® FLEX SB™, SPARTACOTE FLEX XT™ and SPARTACOTE FLEX PURE™ polyaspartic coatings.

Pigmented Coatings: Add full contents of SPARTACOTE Polyaspartic Pigments directly into short filled Part A Tint Base. Mix pigment into Part A with a slow speed drill mixer for 2 minutes to fully disperse the resin pigments. Failure to properly mix pigments may lead to an inconsistent finish and reduced product performance.

6. AVAILABILITY AND COST

Availability

SPARTACOTE and LATICRETE® materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.866.966.1329

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.spartacote.com.

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 420 "SPARTACOTE Floor Maintenance Guide" available at www.spartacote.com for more information.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.866.966.1329

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.spartacote.com.

10. FILING SYSTEM

Additional product information is available on our website at www.spartacote.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 086.4: SPARTACOTE FLEX SB™

DS 086.5: SPARTACOTE FLEX XT™

DS 086.6: SPARTACOTE FLEX PURE™

TDS 420: SPARTACOTE Floor Maintenance Guide

SPARTACOTE

A product brand of LATICRETE International, Inc.

LATICRETE International, Inc. • One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

©2015 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.